



型號 bearing number	主要尺寸(mm)				基本額定負荷(kg)		容許回轉數(rpm)		重量 weight (g)
	內徑 Bore	外徑 Outer diameter	厚度 Width	倒角 Radius	動負荷 Dynamic	靜負荷 Static	脂潤滑 RS, Z 2-RS, ZZ	油潤滑 開放形 open	
	d	D	W	r	C	C0			
6200	10	30	9	0.6	520	245	15000	29000	32
6201	12	32	10	0.6	690	310	13000	27000	37
6201-1/2	12.7	32	10	0.6	690	310	13000	27000	37
6201-13	13	32	10	0.6	690	310	13000	27000	37
6202	15	35	11	0.6	780	380	12000	24000	45
6202-1/2	12.7	35	111	0.6	780	380	12000	24000	50
6202-5/8	15.875	35	11	0.6	780	380	12000	24000	41
6202-16	16	35	11	0.6	780	380	12000	24000	41
6203	17	40	12	0.6	975	490	10000	21000	65
6203-1/2	12.7	40	12	0.6	975	490	10000	21000	70
6203-15	15	40	12	0.6	975	490	10000	21000	67
6203-5/8	15.875	40	12	0.6	975	490	10000	21000	68
6203-16	16	40	12	0.6	975	490	10000	21000	68
6203-3/4	19.05	40	12	0.6	975	490	10000	21000	66
6204-3/4	19.05	47	14	1	1310	680	8700	17000	107
6204	20	47	14	1	1310	680	8700	17000	106
62/22	22	50	14	1	1310	680	8700	17000	104
6204-7/8	22.225	47	14	1	1310	680	8700	17000	104
6205	25	52	15	1	1430	800	7700	15000	128
6205-1	25.4	52	15	1	1430	800	7700	15000	127
62/28	28	58	16	1	1430	800	7700	14000	150
6206	30	62	16	1	1980	1150	6400	13000	199
6207	35	72	17	1.1	2620	1570	5500	11000	288
6208	40	80	18	1.1	2970	1820	5000	11000	366
6209	45	85	19	1.1	3330	2070	4600	9200	407
6210	50	90	20	1.1	3580	2370	4200	8500	463
6211	55	100	21	1.5	4420	3000	3800	7600	608
6212	60	110	22	1.5	5350	3690	3400	6900	622
6213	65	120	23	1.5	5840	4090	3200	6400	990
6214	70	125	24	1.5	6340	4490	3100	6100	1071
6215	75	130	25	1.5	6880	4920	2900	5800	1180
6216	80	140	26	2	7410	5400	2700	5400	1403
6217	85	150	28	2	8560	6310	2500	5000	1793
6218	90	160	30	2	9790	7300	2400	4700	2152
6219	95	170	32	2.1	11100	8350	2200	4400	2624
6220	100	180	34	2.1	12500	9490	2100	4200	3133
6221	105	190	36	2.1	13600	10700	2000	3900	3696
6222	110	200	38	2.1	14700	12000	1800	3700	4363
6224	120	215	40	2.1	15800	13400	1700	3400	5176
6226	130	230	40	3	17000	14900	1600	3200	5811
6228	140	250	42	3	17000	15300	1500	2900	7491
6230	150	270	45	3	18000	17100	-	2700	9398
6232	160	290	48	3	18900	19000	-	2500	14301
6234	170	310	52	4	21700	22800	-	2300	17524
6236	180	320	52	4	23200	24600	-	2200	18296
6238	190	340	55	4	26100	28800	-	-	23018
6240	200	360	58	4	27500	31700	-	-	28239