



●外環無設計公差 TAF(NK) / ●內環無設計公差 TAF(NKI)



NEEDLE ROLLER BEARINGS WITHOUT INNER RING: NK4KS



NEEDLE ROLLER BEARINGS WITH INNER RING: NK4KIS

●外環無設計公差 TAF(NK) ●內環無設計公差

型號 Bearing Number	內徑 Bw	外徑 D	厚度 C	鋼球 φ	鋼球直徑 Cs	鋼球直徑 Cs	標準公差 Ck	重量 (g) Weight
+NK 5/10 TN	5	10	10	0.15	2350	1920	39000	3.1
+NK 5/12 TN	5	10	12	0.15	3000	2650	39000	3.3
+NK 6/10 TN	6	12	10	0.15	2600	2280	17000	4.7
+NK 6/12 TN	6	12	12	0.15	3350	3150	17000	5.7
+NK 7/10 TN	7	14	10	0.3	2850	2650	34000	6.9
+NK 7/12 TN	7	14	12	0.3	3650	3600	34000	8.2
+NK 8/12 TN	8	15	12	0.3	3900	4180	12000	8.7
+NK 8/16 TN	8	15	16	0.3	5100	5800	12000	12
+NK 8/18 TN	8	16	13	0.3	5800	4700	12000	-
+NK 9/12 TN	9	16	12	0.3	4500	5000	31000	10.1
+NK 9/16 TN	9	16	16	0.3	2900	7100	13000	12.8
+NK 10/12 TN	10	17	12	0.3	4750	5500	29000	10.1
+NK 10/16 TN	10	17	16	0.3	4200	7800	29000	13.3
+NK 8/10 TN	10	19	13	0.3	5800	8000	29000	-
NK 12/16	12	19	12	0.3	4400	7100	27000	12.1
NK 12/18	12	19	16	0.3	6000	11000	27000	15.9
+NK 8/12 TN	12	22	16	0.3	9600	10400	26000	-
NK 14/16	14	22	16	0.3	10100	11500	25000	20.7
NK 14/20	14	22	20	0.3	12800	15800	25000	25.5
+NK 8/14	14	25	16	0.6	14400	13800	24000	-
NK 15/16	15	23	16	0.3	10700	12700	24000	21.8
NK 15/20	15	23	20	0.3	13600	17200	24000	26.6
+NK S 15	15	26	16	0.6	14400	14800	23000	-
NK 16/16	16	24	16	0.3	11200	17900	23000	25.4
NK 16/20	16	24	20	0.3	14400	18800	23000	28.4
+NK S 16	16	28	16	0.6	15700	15800	22000	-
NK 17/16	17	25	16	0.3	11900	15000	23000	23.7
NK 17/20	17	25	20	0.3	15100	20400	23000	28.1
NK 18/16	18	26	16	0.3	12500	16200	22000	24.9
NK 18/20	18	26	20	0.3	15800	22000	22000	31.4
+NK S 18	18	30	16	0.3	14800	17700	21000	-
NK 19/16	19	27	16	0.3	13800	17400	22000	26.1
NK 19/20	19	27	20	0.3	16500	23600	22000	32.2
NK 20/16	20	28	16	0.3	13000	17500	21000	27
NK 20/20	20	28	20	0.3	16400	23800	21000	33.9
+NK S 20	20	32	20	0.6	23000	25400	20000	48.7
NK 21/16	21	29	16	0.3	13500	17800	21000	28.1
NK 21/20	21	29	20	0.3	17100	25500	21000	35.2
NK 22/16	22	30	16	0.3	14000	19900	20000	30
NK 22/20	22	30	20	0.3	17700	27000	20000	37
NK S 22	22	33	20	0.6	24500	26500	18000	46.3
NK 24/16	24	32	16	0.3	15800	22300	18000	31.9
NK 24/20	24	32	20	0.3	19800	30500	18000	40
NK S 24	24	34	20	0.6	26000	31000	17000	63.5
NK 25/16	25	33	16	0.3	14900	20600	18000	32.6
NK 25/20	25	33	20	0.3	18800	30500	18000	42
NK S 25	25	38	20	0.6	27500	33500	17000	68.1
NK 26/16	26	34	16	0.3	15300	22600	17000	34
NK 26/20	26	34	20	0.3	19600	32600	17000	42.1
NK 28/20	28	37	20	0.3	22000	34000	16000	52.5
NK 28/30	28	37	30	0.3	33000	57000	16000	82
NK S 28	28	42	20	0.6	28500	36500	15000	83.6
NK 29/20	29	38	20	0.3	21000	34800	15000	58.7
NK 29/30	29	38	30	0.3	32500	57000	15000	84.5
NK 30/20	30	40	20	0.3	22000	36000	15000	65
NK 30/30	30	40	30	0.3	33500	60000	15000	97.9
NK S 30	30	45	22	0.6	32800	40400	14000	85
NK 32/20	32	42	20	0.3	23100	37500	14000	68
NK 32/30	32	42	30	0.3	34500	63000	14000	102
NK S 32	32	47	22	0.6	33500	43500	13000	110
NK 35/20	35	45	20	0.3	24500	41500	13000	73.8
NK 35/30	35	45	30	0.3	36500	69000	13000	123
NK S 35	35	50	22	0.6	35000	47000	12000	118
NK 37/20	37	47	20	0.3	24900	43500	12000	77
NK 37/30	37	47	30	0.3	37000	78000	12000	113
NK S 37	37	52	22	0.6	36500	50000	12000	123
NK 38/20	38	48	20	0.3	25500	45000	12000	79.4
NK 38/30	38	48	30	0.3	38000	76000	12000	116
NK 40/20	40	50	20	0.3	26000	47000	11000	82.7
NK 40/30	40	50	30	0.3	39000	79000	11000	120
NK S 40	40	55	22	0.6	38000	54000	11000	129
NK 42/20	42	52	20	0.3	36500	49000	11000	85.8
NK 42/30	42	52	30	0.3	39500	82000	11000	130
NK 43/20	43	53	20	0.3	37000	51000	11000	86
NK 42/30	43	53	30	0.3	40500	85000	11000	133
NK S 43	43	58	22	0.6	39000	57000	10000	139
NK 45/20	45	55	20	0.3	37500	53000	10000	91.5
NK 45/30	45	55	30	0.3	41000	60000	10000	139
NK S 45	45	60	22	0.6	40500	60000	10000	145
NK 47/20	47	57	20	0.3	38500	56000	10000	94.5
NK 47/30	47	57	30	0.3	43000	94000	10000	142
NK S 47	47	62	25	0.6	38000	54000	9000	158
NK 50/25	50	62	35	0.6	55000	106000	9000	223
NK S 50	50	65	22	1	42500	67000	9000	157
NK 55/25	55	68	25	0.6	40000	82000	8500	180
NK 55/35	55	68	35	0.6	53000	110000	8500	228
NK S 55	55	72	22	1	43000	74000	8000	223

●外環無設計公差 TAF(NK) ●內環無設計公差

型號 Bearing Number	內徑 Bw	內環厚度 F	外徑 D	厚度 C	鋼球 φ	鋼球直徑 Cs	鋼球直徑 Cs	標準公差 Ck	重量 (g) Weight
HERBOR	5	8	12	12	0.3	3950	4100	32000	-
HERBOR	5	8	16	16	0.3	5100	5900	32000	-
HERBOR	6	9	12	12	0.3	4300	5400	21000	120
HERBOR	6	9	16	16	0.3	5900	7100	29000	-
HERBOR	6	10	13	13	0.3	5800	6000	29000	-
HERBOR	7	10	12	12	0.3	4750	5100	29000	-
HERBOR	7	10	16	16	0.3	6200	7400	29000	-
HERBOR	7	12	16	16	0.6	9600	10400	29000	-
NKI S 8	8	14	16	16	0.6	14400	15800	24000	46
NKI 9/12	9	12	12	12	0.3	6400	7100	27000	14.6
NKI 9/16	9	12	16	16	0.3	6900	11000	27000	-
NKI S 9	9	15	16	16	0.6	14800	14800	23000	-
NKI 10/16	10	14	16	16	0.3	10100	11500	25000	27.3
NKI 10/20	10	14	20	20	0.3	12800	15600	25000	-
ENK S 10	10	16	16	16	0.6	15700	15400	23000	-
NKI 12/16	12	16	16	16	0.3	11300	12900	23000	23
NKI 12/20	12	16	20	20	0.3	14400	18800	23000	39
ENK S 12	12	18	16	16	0.6	16800	17700	21000	58
NKI 15/16	15	19	16	16	0.3	13800	17400	23000	38
NKI 15/20	15	19	20	20	0.3	16500	22400	22000	45.7
ENK S 15	15	22	20	20	0.6	24500	28000	18000	90
NKI 17/16	17	21	16	16	0.3	13500	16700	21000	41.4
NKI 17/20	17	21	20	20	0.3	17100	25500	21000	-
NK S 17	17	24	20	20	0.6	20900	31000	17000	-
NKI 20/16	20	24	32	16	0.3	15900	22300	18000	48.5
NKI 20/20	20	24	32	20	0.3	19000	30500	18000	-
ENK S 20	20	28	42	20	0.6	28500	36500	15000	119
NKI 22/16	22	26	16	16	0.3	15300	22600	17000	50
NKI 22/20	22	26	34	20	0.3	19400	32000	17000	-
NKI 25/20	25	29	38	20	0.3	21900	34000	15000	-
NKI 25/30	25	29	38	30	0.3	32500	57000	15000	115
ENK S 25	25	32	47	22	0.6	33600	45500	14000	-
NKI 28/20	28	32	42	20	0.3	23100	37500	14000	-
NKI 28/30	28	32	42	30	0.3	34500	63000	14000	-
NKI 30/20	30	35	45	20	0.3	24300	41500	13000	-
NKI 30/30	30	35	45	30	0.3	36500	69000	13000	-
ENK S 30	30	37	52	22	0.6	36500	50000	12000	-
NKI 32/20	32	37	47	20	0.3	24900	43500	12000	101
NKI 32/30	32	37	47	30	0.3	37000	78000	12000	-
NKI 35/20	35	40	50	20	0.3	26000	47000	11000	-
NKI 35/30	35	40	50	30	0.3	39000	79000	11000	165
NK S 35	35	43	58	22	0.6	39000	57000	10000	210