


▲ GE ES

- » 外圈有一道軸向縫。
- » ES型內圈和外圈有潤滑油槽和油孔。
- » 2RS型外圈兩面帶密封圈。
- » 內外圈表面磷化處理。



▲ GE UK

- » 外圈擠壓成型。
- » 外圈球面襯有PTFE合成材料。
- » 內圈球面鍍鉻

GE ES規格表

| 型號                 | 尺寸mm |     |     |    |      |     |     |           | 負荷KN |      | 重量kg  |
|--------------------|------|-----|-----|----|------|-----|-----|-----------|------|------|-------|
|                    | d    | D   | B   | C  | dk   | R1s | R2s | $\alpha$  | 動    | 靜    |       |
|                    |      |     |     |    |      | min | min | $\approx$ | C    | C0   |       |
| GE6E               | 6    | 14  | 6   | 4  | 10   | 0.3 | 0.3 | 13        | 3.4  | 17   | 0.004 |
| GE8E               | 8    | 16  | 8   | 5  | 13   | 0.3 | 0.3 | 15        | 5.5  | 27.5 | 0.007 |
| GE10E              | 10   | 19  | 9   | 6  | 16   | 0.3 | 0.3 | 12        | 8.15 | 40.5 | 0.011 |
| GE12E              | 12   | 22  | 10  | 7  | 18   | 0.3 | 0.3 | 11        | 10.8 | 54   | 0.016 |
| GE15ES GE15ES2RS   | 15   | 26  | 12  | 9  | 22   | 0.3 | 0.3 | 8         | 17   | 85   | 0.025 |
| GE16ES GE16ES2RS   | 16   | 30  | 14  | 10 | 25   | 0.3 | 0.3 | 10        | 21.2 | 106  | 0.041 |
| GE17ES GE17ES2RS   | 17   | 30  | 14  | 10 | 25   | 0.3 | 0.3 | 10        | 21.2 | 106  | 0.041 |
| GE20ES GE20ES2RS   | 20   | 35  | 16  | 12 | 29   | 0.6 | 0.3 | 9         | 30   | 146  | 0.061 |
| GE25ES GE25ES2RS   | 25   | 42  | 20  | 16 | 35.5 | 0.6 | 0.6 | 7         | 48   | 240  | 0.11  |
| GE30ES GE30ES2RS   | 30   | 47  | 22  | 18 | 40.7 | 0.6 | 0.6 | 6         | 62   | 310  | 0.14  |
| GE35ES GE35ES2RS   | 35   | 55  | 25  | 20 | 47   | 0.6 | 1   | 6         | 80   | 400  | 0.22  |
| GE40ES GE40ES2RS   | 40   | 62  | 28  | 22 | 53   | 0.6 | 1   | 7         | 100  | 500  | 0.3   |
| GE45ES GE45ES2RS   | 45   | 68  | 32  | 25 | 60   | 0.6 | 1   | 7         | 127  | 640  | 0.4   |
| GE50ES GE50ES2RS   | 50   | 75  | 35  | 28 | 66   | 0.6 | 1   | 6         | 156  | 780  | 0.54  |
| GE60ES GE60ES2RS   | 60   | 90  | 44  | 36 | 80   | 1   | 1   | 6         | 245  | 1220 | 1     |
| GE70ES GE70ES2RS   | 70   | 105 | 49  | 40 | 92   | 1   | 1   | 6         | 315  | 1560 | 1.5   |
| GE80ES GE80ES2RS   | 80   | 120 | 55  | 45 | 105  | 1   | 1   | 6         | 400  | 2000 | 2.2   |
| GE90ES GE90ES2RS   | 90   | 130 | 60  | 50 | 115  | 1   | 1   | 5         | 490  | 2450 | 2.7   |
| GE100ES GE100ES2RS | 100  | 150 | 70  | 55 | 130  | 1   | 1   | 7         | 610  | 3050 | 4.3   |
| GE110ES GE110ES2RS | 110  | 160 | 70  | 55 | 140  | 1   | 1   | 6         | 655  | 3250 | 4.7   |
| GE120ES GE120ES2RS | 120  | 180 | 85  | 70 | 160  | 1   | 1   | 6         | 950  | 4750 | 8     |
| GE140ES GE140ES2RS | 140  | 210 | 90  | 70 | 180  | 1   | 1   | 7         | 1080 | 5400 | 11    |
| GE160ES GE160ES2RS | 160  | 230 | 105 | 80 | 200  | 1   | 1   | 8         | 1360 | 6800 | 14    |
|                    |      |     |     |    |      |     |     |           |      |      |       |

GE UK規格表

| 型号     | 尺寸mm |    |    |    |     |      |     |     |    | 负荷KN |     | 重量kg  |
|--------|------|----|----|----|-----|------|-----|-----|----|------|-----|-------|
|        | d    | D  | B  | C  | d1  | dk   | R1s | R2s | α  | 动    | 静   |       |
|        |      |    |    |    | min |      | min | min | ≈  | C    | C0  |       |
| GE6UK  | 6    | 14 | 6  | 4  | 8   | 10   | 0.3 | 0.3 | 13 | 3.6  | 9.1 | 0.004 |
| GE8UK  | 8    | 16 | 8  | 5  | 10  | 13   | 0.3 | 0.3 | 15 | 5.8  | 14  | 0.008 |
| GE10UK | 10   | 19 | 9  | 6  | 13  | 16   | 0.3 | 0.3 | 12 | 8.6  | 21  | 0.011 |
| GE12UK | 12   | 22 | 10 | 7  | 15  | 18   | 0.3 | 0.3 | 10 | 11   | 28  | 0.015 |
| GE15UK | 15   | 26 | 12 | 9  | 18  | 22   | 0.3 | 0.3 | 8  | 18   | 45  | 0.027 |
| GE17UK | 17   | 30 | 14 | 10 | 20  | 25   | 0.3 | 0.3 | 10 | 22   | 56  | 0.041 |
| GE18UK | 18   | 33 | 20 | 16 | 20  | 25   | 0.5 | 0.5 | 10 | 27   | 64  | 0.076 |
| GE20UK | 20   | 35 | 16 | 12 | 24  | 29   | 0.3 | 0.3 | 9  | 31   | 78  | 0.066 |
| GE25UK | 25   | 42 | 20 | 16 | 29  | 35.5 | 0.6 | 0.6 | 7  | 51   | 127 | 0.119 |
| GE30UK | 30   | 47 | 22 | 18 | 34  | 40.7 | 0.6 | 0.6 | 6  | 65   | 166 | 0.163 |