


▲ GE ES



▲ GE UK

>> The outer ring has an axial seam.
 >> ES type inner ring and outer ring has lubricating oil groove and oil hole.
 >> 2RS outer ring has seals on both sides.
 >> Internal and outer ring surface has phosphate treatment.

>> Outer ring extrusion.
 >> Outer spherical lined with P TFE synthetic village material
 >> Inner ring surface is chrome plated

GE ES規格表

型號	尺寸mm								負荷KN		重量kg
	d	D	B	C	dk	R1s	R2s	α	動	靜	
					min	min	min	$\approx$	C	C0	
GE6E	6	14	6	4	10	0.3	0.3	13	3.4	17	0.004
GE8E	8	16	8	5	13	0.3	0.3	15	5.5	27.5	0.007
GE10E	10	19	9	6	16	0.3	0.3	12	8.15	40.5	0.011
GE12E	12	22	10	7	18	0.3	0.3	11	10.8	54	0.016
GE15ES GE15ES2RS	15	26	12	9	22	0.3	0.3	8	17	85	0.025
GE16ES GE16ES2RS	16	30	14	10	25	0.3	0.3	10	21.2	106	0.041
GE17ES GE17ES2RS	17	30	14	10	25	0.3	0.3	10	21.2	106	0.041
GE20ES GE20ES2RS	20	35	16	12	29	0.6	0.3	9	30	146	0.061
GE25ES GE25ES2RS	25	42	20	16	35.5	0.6	0.6	7	48	240	0.11
GE30ES GE30ES2RS	30	47	22	18	40.7	0.6	0.6	6	62	310	0.14
GE35ES GE35ES2RS	35	55	25	20	47	0.6	1	6	80	400	0.22
GE40ES GE40ES2RS	40	62	28	22	53	0.6	1	7	100	500	0.3
GE45ES GE45ES2RS	45	68	32	25	60	0.6	1	7	127	640	0.4
GE50ES GE50ES2RS	50	75	35	28	66	0.6	1	6	156	780	0.54
GE60ES GE60ES2RS	60	90	44	36	80	1	1	6	245	1220	1
GE70ES GE70ES2RS	70	105	49	40	92	1	1	6	315	1560	1.5
GE80ES GE80ES2RS	80	120	55	45	105	1	1	6	400	2000	2.2
GE90ES GE90ES2RS	90	130	60	50	115	1	1	5	490	2450	2.7
GE100ES GE100ES2RS	100	150	70	55	130	1	1	7	610	3050	4.3
GE110ES GE110ES2RS	110	160	70	55	140	1	1	6	655	3250	4.7
GE120ES GE120ES2RS	120	180	85	70	160	1	1	6	950	4750	8
GE140ES GE140ES2RS	140	210	90	70	180	1	1	7	1080	5400	11
GE160ES GE160ES2RS	160	230	105	80	200	1	1	8	1360	6800	14

GE UK規格表

型号	尺寸mm									负荷KN		重量kg
	d	D	B	C	d1	dk	R1s	R2s	α	动	静	
					min		min	min	≈	C	C0	
GE6UK	6	14	6	4	8	10	0.3	0.3	13	3.6	9.1	0.004
GE8UK	8	16	8	5	10	13	0.3	0.3	15	5.8	14	0.008
GE10UK	10	19	9	6	13	16	0.3	0.3	12	8.6	21	0.011
GE12UK	12	22	10	7	15	18	0.3	0.3	10	11	28	0.015
GE15UK	15	26	12	9	18	22	0.3	0.3	8	18	45	0.027
GE17UK	17	30	14	10	20	25	0.3	0.3	10	22	56	0.041
GE18UK	18	33	20	16	20	25	0.5	0.5	10	27	64	0.076
GE20UK	20	35	16	12	24	29	0.3	0.3	9	31	78	0.066
GE25UK	25	42	20	16	29	35.5	0.6	0.6	7	51	127	0.119
GE30UK	30	47	22	18	34	40.7	0.6	0.6	6	65	166	0.163